



HT702/704

An easy-to-use 2/4 port ATA

The HT702/704 is a 2/4 port analog telephone adapter (ATA) that allows users to create a high-quality and manageable IP telephony solution for residential and office environments. Its ultra-compact size, voice quality, advanced VoIP functionality, security protection and auto provisioning options enable users to take advantage of VoIP on analog phones and enables service providers to offer high quality IP service. The HT702/704 is an ideal ATA for individual use and for large scale commercial IP voice deployments.



Supports 2 SIP profiles through 2 or 4 FXS port and single 10/100Mbps port



TLS and SRTP security encryption technology to protect calls and accounts



Automated provisioning options include TR-069 and XML config files



3 WAY
Supports 3-way voice conferencing



Failover SIP server automatically switches to secondary server if main server loses connection



Supports T.38 Fax for creating Fax-over-IP



Supports a wide range of caller ID formats



Use with Grandstream's UCM series of IP PBXs for Zero Configuration provisioning



Supports advanced telephony features, including call transfer, call forward, call-waiting, do not disturb, message waiting indication, multi-language prompts, flexible dial plan and more

Interfaces	
Telephone Interfaces	Two (2) FXS port (HT702) or four (4) FXS ports (HT704)
Network Interfaces	One (1) 10/100Mbps auto-sensing ethernet ports (RJ45)
LED Indicators	Power, Internet, LINK/ACT, PHONE 1/PHONE 1 (HT702), PHONE 1/PHONE 2/PHONE 3/ PHONE 4 (HT704)
Factory Reset Button	Yes
Voice, Fax, Modem	
Telephony Features	Caller ID display or block, call waiting, flash, blind or attended transfer, forward, hold, do not disturb, 3-way conference
Voice Codecs	G.711 with Annex I (PLC) and Annex II (VAD/CNG), G.723.1, G.729A/B, G.726, iLBC, dynamic jitter buffer, advanced line echo cancellation
Fax Over IP	T.38 compliant Group 3 fax relay up to 14.4kbps and auto-switch to G.711 for fax pass through
Short/Long Haul Ring Load	3REN: Up to 1km on 24 AWG
Caller ID	Bellcore type 1 & 2, ETSI, BT, NTT and DTMF-based CID
Disconnect Methods	Busy Tone, Polarity Reversal/Wink, Loop Current
Signaling	
Network Protocols	TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS, DHCP, NTP, TFTP, TELNET, PPPoE, STUN, SIP (RFC3261), SIP over TCP/TLS, SRTP, TR069
QoS	Layer 2 (802.1Q VLAN/802.1p) and Layer 3 (ToS, Diffserv, MPLS)
DTMF Method	In-Audio, RFC2833 and/or SIP INFO
Provisioning and Control	HTTP, HTTPS, TELNET, TFTP, TR069, secure and automated provisioning using AES encryption, syslog
Security	
Media	SRTP
Control	TLS/SIPS/HTTPS
Management	Syslong support, telnet, remote management using web browser
Physical	
Universal Power Supply	Input: 100-240VAC, 50-60Hz Output: 12V VDC, 0.5A (HT702), 1A (HT704)
Environmental	Operational: 32° ~ 104°F or 0° ~ 40°C; Storage: -14° ~ 140°F or -10°~ 60°C; Humidity: 10 - 90% non condensing
Dimension and Weight	119mm x 78mm x 60mm, 0.31kg (with package)
Compliance	FCC (Part 68 & 15B), C-Tick, AS/NZS CISPR22, CISPR24, CE, EN55022, EN55024, TBR21, EN60950, EN61000-3-2, EN61000-3-3, UL (Power supply)